

POLI MONO DOCKING STATION MP400T

for Multi gas detectors



KEY FEATURES

- **Simple & Fast:** One-button operation for either bump test or calibration
- **High Capacity:** 2,000 calibration or bump record storage in reliable FLASH Memory
- **Convenient:** Records can be downloaded without the POLI in place
- **Portable:** Battery power for up to 1000 bump tests
- **Robust:** All-in-one hard case

The POLI MonoDock (MP400T) is a docking and calibration station for the POLI Multi-Gas Detectors. The MP400T provides fast and easy calibration or bump testing: just place the POLI in the bay, connect the cable, and push start. All calibrations and bump test results are stored in on-board memory as a compliance record downloadable separate from the instruments themselves. The docking station is designed to operate with the four commonly measured gases oxygen (O₂), carbon monoxide (CO), hydrogen sulfide (H₂S), methane (CH₄), ammonia (NH₃), hydrogen cyanide (HCN), plus isobutylene for PID, and several other toxic gases. The MonoDock has rechargeable batteries and is portable for remote use. Two versions of the MonoDock are offered: one for pumped POLI instruments and one for diffusion POLI instruments.

POLI MONO DOCKING STATION MP400T

for Multi gas detectors



POLI MONODOCK MP400T SPECIFICATIONS

Size	9.2 x 7.5 x 4.3 in (23.5 x 19.0 x 10.7 cm)
Weight	4.4 lbs. (2.0 kg)
Number of Units	One (1) POLI Pump Monitor
Battery	Rechargeable Lithium battery, up to 1000 bump tests on a single charge
Temperature	32°F to 122°F (0°C to 50°C)
Humidity	5 to 95% relative humidity (non-condensing)
Event Log	2000 Calibration or Bump records
Power & Communications Connection	USB (Type A)
Test Gas Supply	• Cylinder(s) & regulator(s) (not included) outside MonoDock • Demand flow regulator(s) preferred • The POLI Monodock is available in two models: • one suitable for pumped POLI devices • one suitable for diffusion (non-pumped) POLI devices.
Gas Connections	• Quick-connects for 6-mm o.d. tubing: • 2 Test gas inlets for calibration/bump • Air inlet for zeroing
Calibration Gases* *Operation with other toxic gases is not available at this time. Check with WatchGas for availability.	• Gas mix with up to 4 gases: • Oxygen (O₂) • Carbon Monoxide (CO) • Hydrogen Sulfide (H₂S) • Methane (CH₄) • Isobutylene (C₄H₈, for PID) • Carbon dioxide (CO₂) • Ammonia (NH₃) • Hydrogen cyanide (HCN) • Nitric oxide (NO) • Phosphine (PH₃) • Sulfur dioxide (SO₂) • Ethylene oxide (ETO) • Methyl mercaptan (CH₃SH) • Tetrahydrothiophene (THT)
Safety Certifications	For use in non-hazardous locations



FOR MORE INFORMATION

www.watchgas.com
info@watchgas.com

Distributed by

WatchGas POLI MonoDock DS EN 15-05-23 V1.1 © 2023 WatchGas B.V.
WatchGas is dedicated to continuously improving its products. Therefore, the specifications and features mentioned in this datasheet are subject to change without prior notice.